



Specification sheet for:



4 3/4" 7:8 Lobe 2.9 Stage PVX (SS) HS88 Group 0

PV475729-HS-0

Rotor Details	
Overall Length (in)	242.0
Head Length (in)	5.50
Head Diameter (in)	2.99
Contour OD (in)	2.798
Ecc (in)	0.163
C to V (in)	2.473
Weight (lbs)	275.0
Std Connection	2 3/8" HEF

Recommended Operating Range	
Flow Rate	100 gpm-250 gpm
No Load RPM	32-80
Displacement	0.32 revs/gal
Max Working Pressure	805 psi
Max Off-BTM Pressure	190 psi
Max Operating Torque	6359 ft-lbs
Torque Slope	8.378 ft-lbs/psi

Max Operating pressure = Max Working psi - Max Off-BTM psi


For maximum life do not exceed 615 psi differential.

Stator Details	
Overall Length (in)	250.0
Tube OD (in)	4.75
Tube ID (in)	3.75
Alternate OD (in)	5.00
Std Cutbacks (in)	8.00
Weight (lbs)	523

Sizing and Fit Information	
Vector Minor (in)	2.477
Shop Fit @ 70°F	- 0.004 Loose
Temp Correction Factor*	5.5

* Temp correction factor is the degrees (F) required to change the stator size by .001" on diameter.

Theoretical performance with water at Operating Temperature



Performance curves for reference only. Data is based on new rotor and stator nominal dimensions. Performance downhole may vary based on drilling conditions and rotor/stator fit. Operating over the specified limits may result in damage to the power section and/or connected components. Information is subject to change.