



Specification sheet for:

5" 6:7 Lobe 8.0 Stage PVX TR75 Group 4



PV500680-TR-4

Rotor Details	
Overall Length (in)	241.0
Head Length (in)	6.00
Head Diameter (in)	2.90
Contour OD (in)	3.018
Ecc (in)	0.192
C to V (in)	2.635
Weight (lbs)	321.0
Std Connection	2 3/8" HEF

Recommended Operating Range	
Flow Rate	150 gpm-350 gpm
No Load RPM	126-294
Displacement	0.84 revs/gal
Max Working Pressure	1357 psi
Max Off-BTM Pressure	224 psi
Max Operating Torque	3829 ft-lbs
Torque Slope	2.954 ft-lbs/psi


Max Operating pressure = Max Working psi - Max Off-BTM psi

For maximum life do not exceed 1133 psi differential.

Stator Details	
Overall Length (in)	250.0
Tube OD (in)	5.00
Tube ID (in)	4.00
Alternate OD (in)	NA
Std Cutbacks (in)	8.00
Weight (lbs)	556

Sizing and Fit Information	
Vector Minor (in)	2.648
Shop Fit @ 70°F	- 0.013 Loose
Temp Correction Factor*	5

\* Temp correction factor is the degrees (F) required to change the stator size by .001" on diameter.



Performance curves for reference only. Data is based on new rotor and stator nominal dimensions. Performance downhole may vary based on drilling conditions and rotor/stator fit. Operating over the specified limits may result in damage to the power section and/or connected components. Information is subject to change.