



PV Fluid Products

SPECIFICATION SHEET FOR: 6 1/4" 7:8 LOBE 4.8 STAGE HS88 GROUP 4

PV625748-HS-4


Rotor Details	
Overall Length (in)	194.5
Head Length (in)	6.00
Head Diameter (in)	3.50
Contour OD (in)	3.980
Ecc (in)	0.225
C to V (in)	3.530
Weight (lbs)	695.0
Std Connection	4" FH

Stator Details	
Overall Length (in)	203.5
Tube OD (in)	6.25
Tube ID (in)	5.00
Alternate OD (in)	6.50
Std Cutbacks (in)	8.00
Weight (lbs)	695

Recommended Operating Range	
Flow Rate	150 gpm-400 gpm
No Load RPM	54-144
Displacement	0.36 revs/gal
Max Working Pressure	1365 psi
Max Off-BTM Pressure	162 psi
Max Operating Torque	10078 ft-lbs
Torque Slope	7.664 ft-lbs/psi
Max Operating pressure = Max Working psi - Max Off-BTM psi	
For Maximum Life do not exceed 1203 psi differential.	

Sizing and Fit Information	
Vector Minor (in)	3.538
Shop Fit @ 70°F	- 0.008 Loose
Temp Correction Factor*	5
* Temp correction factor is the degrees (F) required to change the stator size by .001" on diameter.	

Theoretical performance with water at Operating Temperature



Performance curves for reference only. Data is based on new rotor and stator nominal dimensions. Performance downhole may vary based on drilling conditions and rotor/stator fit. Operating over the specified limits may result in damage to the power section and/or connected components. Information is subject to change.