



Specification sheet for:

6 3/4" 7:8 Lobe 2.9 Stage PVX (SS) TR75 Group 4

PV675729-TR-4



Rotor Details	
Overall Length (in)	213.5
Head Length (in)	7.00
Head Diameter (in)	4.00
Contour OD (in)	4.296
Ecc (in)	0.244
C to V (in)	3.808
Weight (lbs)	609.0
Std Connection	2 7/8" Reg

Recommended Operating Range	
Flow Rate	300 gpm-600 gpm
No Load RPM	42-84
Displacement	0.14 revs/gal
Max Working Pressure	575 psi
Max Off-BTM Pressure	159 psi
Max Operating Torque	8035 ft-lbs
Torque Slope	15.363 ft-lbs/psi


Max Operating pressure = Max Working psi - Max Off-BTM psi

For maximum life do not exceed 416 psi differential.

Stator Details	
Overall Length (in)	220.0
Tube OD (in)	6.75
Tube ID (in)	5.50
Alternate OD (in)	NA
Std Cutbacks (in)	8.00
Weight (lbs)	833

Sizing and Fit Information	
Vector Minor (in)	3.836
Shop Fit @ 70°F	- 0.028 Loose
Temp Correction Factor*	4

* Temp correction factor is the degrees (F) required to change the stator size by .001" on diameter.



Performance curves for reference only. Data is based on new rotor and stator nominal dimensions. Performance downhole may vary based on drilling conditions and rotor/stator fit. Operating over the specified limits may result in damage to the power section and/or connected components. Information is subject to change.