



Specification sheet for:

6 3/4" 7:8 Lobe 3.3 Stage (SS) HS88 Group 0



PV675733-HS-0

Rotor Details	
Overall Length (in)	238.5
Head Length (in)	7.50
Head Diameter (in)	4.00
Contour OD (in)	4.500
Ecc (in)	0.255
C to V (in)	3.990
Weight (lbs)	663.0
Std Connection	2 7/8" Reg

Recommended Operating Range	
Flow Rate	300 gpm-600 gpm
No Load RPM	51-102
Displacement	0.17 revs/gal
Max Working Pressure	945 psi
Max Off-BTM Pressure	216 psi
Max Operating Torque	15610 ft-lbs
Torque Slope	17.84 ft-lbs/psi

Max Operating pressure = Max Working psi - Max Off-BTM psi


For maximum life do not exceed 729 psi differential.

Stator Details	
Overall Length (in)	245.0
Tube OD (in)	6.75
Tube ID (in)	5.50
Alternate OD (in)	NA
Std Cutbacks (in)	8.00
Weight (lbs)	912

Sizing and Fit Information	
Vector Minor (in)	3.987
Shop Fit @ 70°F	0.003 Compression
Temp Correction Factor*	5

* Temp correction factor is the degrees (F) required to change the stator size by .001" on diameter.

Theoretical performance with water at Operating Temperature



Performance curves for reference only. Data is based on new rotor and stator nominal dimensions. Performance downhole may vary based on drilling conditions and rotor/stator fit. Operating over the specified limits may result in damage to the power section and/or connected components. Information is subject to change.